



NSK 6020VV deep groove ball bearings

Bearing No. 6020VV

6020VV Bearing 2D drawings and 3D CAD models

Size	100x150x24 mm
Bore Diameter	100 mm
Outer Diameter	150 mm
Width	24 mm
d	100 mm
D	150 mm
B	24 mm
C	24 mm
r min.	1,5 mm
da min.	108 mm
da max	112,5 mm
Da max.	142 mm
ra max.	1,5 mm
Weight	1,29 Kg
Basic dynamic load rating (C)	60 kN
Basic static load rating (C0)	54 kN
(Grease) Lubrication Speed	4 300 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.455
EAN	0029176531835
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0



TZR?Bearing Machine Development Co.,...

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	100MM Bore; 150MM Outside Diameter; 24MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nskamericas.com
Manufacturer Item Number	6020VV
Weight / LBS	1.24
Outer Race Width	0.945 Inch 24 Millimeter
Bore	3.937 Inch 100 Millimeter
Outside Diameter	5.906 Inch 150 Millimeter
SRI	7.8
hidYobi	6020VV
LangID	1
D_	150
SREX	0.03
B_	24



TZR? Bearing Machine Development Co.,...

da min	108
hidTable	ecat_NS RDGB
SRE	7.8
mass	1.29
GRS rpm	4300
ra	1.5
SRIX	0.03
D_a	142
SRIN	-0.03
C0	54
fo	15.9
SREN	-0.03
DE_	140.081
Prod_Type3	DGBB_SR_VV
DA_	15.081
bomp	0
Z_	15
yobi	6020VV
C_conv	60000
ALPHA_	0
SDM_	125
r	1.5
KBRG	6151
SBRG	10
DI_	109.919