




TZR Bearing Machine Development Co.,...



NUP307 Bearing 2D drawings and 3D CAD models

NTN NUP307 cylindrical roller bearings

Bearing No. NUP307

Size	35x80x21 mm
Bore Diameter	35,000 mm
Outer Diameter	80,000 mm
Width	21,000 mm
d	35,000 mm
D	80,000 mm
B	21,000 mm
C	21,000 mm
Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.51
EAN	4547359135879
Product Group	B04144
Bore Profile	Straight
Cage Material	Steel
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	No
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes



TZR Bearing Machine Development Co.,...

Inch - Metric	Metric
Other Features	1 Rib Inner Ring with Side Plate 2 Rib Outer Ring Cage On Outer Ring ID
Long Description	35MM Bore; Straight Bore Profile; 80MM Outside Diameter; 21MM Width; Steel Cage Material; RBEC 1 ISO P0; Single Row; Not Separable; No Snap Ring; Relubricatable; C3-Loose Internal Clearance; Retain
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	NUP307
Weight / LBS	1.114
Bore	1.378 Inch 35 Millimeter
Outside Diameter	3.15 Inch 80 Millimeter
Width	0.827 Inch 21 Millimeter
bore diameter:	35 mm
static load capacity:	47000 N
outside diameter:	80 mm
precision rating:	ISO Class 0
overall width:	21 mm
maximum rpm:	11000 rpm
flanges:	(2) Outer Ring, (2) Inner Ring
bearing material:	Hardened Alloy Steel
bore type:	Straight
cage material:	Pressed Steel
number of rows:	1



TZR Bearing Machine Development Co.,...

finish/coating:	Uncoated
internal clearance:	CN
closure type:	Open
ring separation:	Separable Inner Ring
fillet radius:	1.5 mm
operating temperature range:	-40 to 120 ° C
manufacturer product page:	Click here
dynamic load capacity:	49500 N