




TZR Bearing Machine Development Co.,...



5206 Bearing 2D drawings and 3D CAD models

Deep Groove Ball Bearing Distributor of NSK
SKF Timken NTN Koyo 5206 5207 5208 5209
5210 ...

Bearing No. 5206

Size	30x62x23.8 mm
Bore Diameter	30 mm
Outer Diameter	62 mm
Width	23.8 mm
d	30 mm
D	62 mm
B	23.8 mm
C	23.8 mm
a	30.8 mm
r min.	1 mm
da min.	35.5 mm
da max	38.6 mm
Da max.	56.5 mm
ra max.	1 mm
Weight	0.290 Kg
Basic dynamic load rating (C)	29.7 kN
Basic static load rating (C0)	21.3 kN
(Grease) Lubrication Speed	6400 r/min
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.321



TZR Bearing Machine Development Co.,...

EAN	0060579003659
Product Group	B00152
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	24 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	30MM Bore; 62MM Outside Diameter; 23.8MM Width; Open; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Steel Cage; 24 Degree; 1 (Single)
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.koyousa.com
Width	0.937 Inch 23.8 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter
Bore	1.181 Inch 30 Millimeter
Bearing No.	5206



TZR Bearing Machine Development Co.,...

r(min)	1
Cr	37.2
C0r	21.3
Cu	1.10
Grease lub.	6400
Oil lub.	8600
da(min)	35.5
da(max)	-
Da(max)	56.5
ra(max)	1
(Refer.) Mass(kg)	0.290